Confined Space Ventilation

Accessories

Vent Flow[™] Alarm Designed to Meet Confined Space Ventilation Flow Loss Alarm Requirements



- Meets Canadian alarm requirements
- Attaches inline to any 8" blower duct. (Optional larger and smaller duct sizes available upon request)
- Operates on two standard 9-volt batteries
- Audible alarm (92dbA) and visual red light activate with approximately 50% flow loss in the duct
- Alarms deactivate when normal flow is re-established
- Galvanized tubular steel housing
- Weight: 7 lbs.
- Overall length, 13"
- No AC power required
 - For Use In Non-Hazardous Locations



SVF-8ALM In Use

Standard Ducting

- · Vinyl polyester ventilation air duct hose
- 8" diameter with external wear strips custom sizes available on request
- Internal steel reinforced wire hoop 5" pitch
- 6" long attachment cuff, 8 3/8" diameter, with adjustable belt straps on both hose ends
- Maximum temperature rating 180°F



Conductive Ducting With Ground Wires Attached to Each End of Wire Helix

8" Duct to Duct Connector

SVH-88C Galvanized Steel or Polyethylene Supplied

8" Conductive **Duct to Duct Connector**



Model No.	Description
	Standard Duct
SVH-3	8 " Diameter - 3 ft. Standard Duct - Yellow
SVH-6	8 ″ Diameter - 6 ft. Standard Duct - Yellow
SVH-15	8 ″ Diameter - 15 ft. Standard Duct - Yellow
SVH-25	8 " Diameter - 25 ft. Standard Duct - Yellow
	Conductive Duct
SVH-CND86	8 ″ Diameter - 6 ft. Conductive Duct - Black
SVH-CND815	8 " Diameter - 15 ft. Conductive Duct - Black
SVH-CND825	8 " Diameter - 25 ft. Conductive Duct - Black
	Duct to Duct Connector
SVH-88C	8 " Duct to Duct Connector
SVH-88CND	8 " Conductive Duct to Duct Connector w/ Ground Lugs

Custom Sizes Available Up To 36" Diameter

Custom Duct Transitions

Enlarging and Reducing Adapters are Available to Accommodate Any Transition Size - Contact **Customer Service for Ordering Information**





SVH-DC25