

### **Model: UTS ergo line M-5**

### **Reference no.: 29-060957-003**

Correct use: passive storage

Product group: safety storage cabinet



Fire resistance (FR): Type 90 , Catalogue page: 123 , Doors can be opened with minimum effort, design: wing door , Door technology: classical , In case of fire, automatic and blockage-free self-closing via thermocouple: yes , Outer width [mm]: 888 - (34.96 inch) , Outer depth [mm]: 493 - (19.41 inch) , Outer height [mm]: 631 - (24.84 inch) , Base height [mm]: 35 , Base version: classical, with slots and floor extraction , Material outer carcass: sheet steel, powder-coated , Gross weight [kg]: 137 - (302.03 lbs) , Number of sides: 1 , Inner width [mm]: 790 - (31.10 inch) , Inner depth [mm]: 363 - (14.29 inch) , Inner height [mm]: 480 - (18.90 inch) , Material inner carcass: decor panels , Maximum volume of the largest individual container [l]: 12 - (3.17 gal) , Collection volume [l]: 13.9 - (3.67 gal) , Shelf type: automatically extending pull-out tray , Number of storage shelves: 1 , Perforated sheet interior: perforated sheet insert , Number of perforated sheet inserts: 1 , Earthing connection according to TRGS 727 available: 2 , Number of earthing connections: 2 , Exhaust air connection included: NW 75 , Standing surface material: sheet steel, powder-coated , Load-bearing capacity per standing surface with uniformly distributed load [kg]: 40 - (88.18 lbs) , Adjustment height 1 left [mm]: 340 - (13.39 inch) , Mark of approval by TÜV: GS mark , Type-tested by recognised test institutes according to: DIN EN 14470-1 , TÜV-tested according to: DIN EN 14470-1, EK5/AK4 09-10 , Further TÜV testing (1): DIN EN 14727 , Further TÜV testing (2): TRGS 510 Annex 3 , Added value mark of approval by TÜV: High Quality , Declaration of conformity: CE