

# MaxiDry®

CONTROLLED PERFORMANCE™



OEKO-TEX®  
CONFIRMED BY TESTS AS  
STANDARD 100

08.014.57867 HOHENSTEIN HTTI

For more information, visit  
[www.oeko-tex.com/standard100](http://www.oeko-tex.com/standard100)

USE (MECHANICAL PROTECTION FOR STYLES: 56-424, 425, 427, 451)  
(MECHANICAL+CHEMICAL PROTECTION FOR STYLES: 56-426, 530, 535)

**Liquid repellent or liquid proof work gloves for CONTROLLED PERFORMANCE™ in oily or wet environments. MaxiDry® Zero™ offers additional thermal resistance up to -10°C. Performance levels relate to the palm area of the glove**

Do not use these gloves to protect against serrated edges or blades or naked flames. MaxiDry® shall not be worn when there is a risk of entanglement by moving parts of machines.

Please ensure that if you are working with chemicals that the gloves have the chemical pictogram printed on the glove and are suitable for the chemical that you are exposed to.

Further information about chemical permeation levels can be found at [www.atg-glovesolutions.com](http://www.atg-glovesolutions.com). This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only and relates only to the chemical tested. It can be different if it be used in a mixture.

Before use, inspect the gloves for any defects or imperfections and avoid wearing damaged, heavily soiled, worn or dirty (also internally) glove of any substance, this could irritate and/or infect the skin and cause dermatitis. In this event, seek medical advice from the company doctor or consult a dermatologist. After use, clean the gloves thoroughly with a dry cloth to remove any contaminants. If the gloves are to be re-worn store in such a way that the inside lining of the support can dry out easily.

Sizing according to EN 420:2003+A1:2009

Size	Minimum length (mm)	Palm circumference (mm)
5 (EU) XXS (US)	210 mm	137 mm
6 (EU) XS (US)	220 mm	152 mm
7 (EU) S (US)	230 mm	178 mm
8 (EU) M (US)	240 mm	203 mm
9 (EU) L (US)	250 mm	229 mm
10 (EU) XL (US)	260 mm	254 mm
11 (EU) XXL (US)	270 mm	279 mm
12 (EU) XXXL (US)	280 mm	295 mm

If the glove length is shorter than mentioned in the table above it suits for special purpose as it only protects the hand, not the cuff area.

## CONSTITUANTS / ALLERGIES

Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

WARNING – THIS PRODUCT MAY CONTAIN NATURAL LATEX WHICH MAY CAUSE AN ALLERGIC REACTION; FOR MORE INFORMATION PLEASE CONTACT ATG@TECHNICAL DEPARTMENT.

## EXPLANATION OF THE PICTOGRAMS

	<b>EN 420:2003+A1 2009</b> General requirements (risk category, sizing, marking, labelling, etc.) Information supplied by the manufacturer in the user notice
	<b>EN 388:2003</b> Mechanical Hazards A: Abrasion resistance - number of rubs (Level 0-4) B: Blade cut resistance - Coupe Test - Index (Level 0-5) C: Tear resistance - N (Level 0-4) D: Puncture resistance N (Level 0-4)
	<b>EN 388:2016</b> Mechanical Hazards A: Abrasion resistance - number of rubs (Level 0-4) B: Blade cut resistance - Coupe Test - Index (Level 0-5) C: Tear resistance - N (Level 0-4) D: Puncture resistance N (Level 0-4) E: TDM Cut resistance according to ISO 13997 - N (Level A-F) F: Impact protection according to EN 13894:2015 - Y/N (P-Yes)
	<b>EN 374:2003 (MaxiDry® 56-426 and MaxiDry® Plus™ 56-530, 535)</b> Low Chemical Resistance Waterproof glove pictogram is under for those gloves that do not achieve a breakthrough time of >30 minutes against at least three chemicals from the defined list of 12, but which comply with the penetration test.
	<b>EN 374:2003 (MaxiDry® Plus™ 56-530, 535)</b> Micro-Organism Hazards Penetration: air and/or water leak test and inspection in compliance with the Acceptable Quality Level (AQL). - Level 3 - AQL <0,65 / G1
	<b>EN 511:2006 (MaxiDry® Zero™ 56-451)</b> Cold Hazards A: Convective cold (0-4) B: Contact cold (0-4) C: Water impermeability(0-1)
	<b>Food Contact (MaxiDry® Zero™ 56-451)</b> Sign shows suitability for direct or indirect food contact. Please visit <a href="http://www.atg-glovesolutions.com">www.atg-glovesolutions.com</a> to determine the suitability by food.
	<b>Production date</b> MM/YYYY

Higher values stand for better protection/resistance. If "X" is marked as a performance level the test is either not applicable or not proceeded. Puncture resistance should not be confused with piercing exerted by thin tips or needles.

## CARE INSTRUCTIONS

### Storage/Cleaning:

Store the gloves in their original packaging in a cool and dry place. Keep away from direct sunlight, heat, flame and sources of Ozone. Gloves can be laundered at 40°C with a standard detergent (3 cycles). Natural drying. (MaxiDry® 56-426 and MaxiDry® Plus™ 56-530, 535 are not designed to be washed as they are for chemical resistance).

Gloves can be used out of the pack 5 years after production date, printed on the glove. Glove life time in use is based on wear, abrasion and for gloves according to EN 374:2003 the breakthrough time for the chemicals used.

### Disposal/Waste:

Used gloves may be contaminated with infectious or hazardous substances, dispose of according to the Local Authority/Municipality Regulations, landfill or incinerate under controlled conditions. For more information on glove selection, usage and performances and for a copy of the CE declaration of conformity please contact ATG® ([info@atg-glovesolutions.com](mailto:info@atg-glovesolutions.com)) or send a fax to: +94-11-225.38.87) or the supplier of these gloves.

## WARRANTY/LIMITATION OF DAMAGES

ATG® warrants that this product shall be in accordance with ATG® standard specifications as of the date of delivery to authorized distributors. Except to the extent prohibited by law, this warranty is in line of all warranties, including any warranty of fitness for a particular purpose; ATG® liability shall be limited to the purchase price of the product at issue. Buyers and users of this product are deemed to have accepted the terms of this limitation of warranty, which may not be varied by any verbal or written agreement.