TankClamp[®]

Mobile Anchor on storage tanks, (concrete) pits, etc.

The TankClamp[®] is a mobile anchor that can be placed over edges of storage tanks, (concrete) pits, beams, walls, etc. TankClamp can be used for both vertical fall arrest, rescue equipment and horizontal life line systems (HLL).

Mobile Anchor facility for:

- · Height Safety devices (inertia reels, etc.)
- Recovery blocks
- · Lanyards
- (Temporary) Horizontal lifeline systems (like HONORope-T)
- $\cdot\,$ Rescue systems and descent device's (evacuation)

TankClamp to be fixed by two steel fixation bolts with locking nuts. To prevent the wear of tank coatings, TankClamp has Erlaton[®] slide parts on the inside of clamp. The TankClamp is approved to be used by 2 people simultaneously.

Recovery Blocks, SRL's, lanyards, rope grip systems, Manriding Winches, Rescue & Evacuation devices can be placed onto the modular TankClamp (also modular with STAR[®]-series devices, FlangeClamp[®], Tripod and Davit)!

Vertical application

The TankClamp (with Intermediate Bracket) & STAR-series devices can be used in a vertical application for safe entry



of confined spaces. After a fall occurred the SRL can also be used for the rescue operations.



Horizontal application

HLL can be installed between two, opposite eachother placed TankClamps. Even a third TankClamp, 90° angle from HLL, with recovery or rescue device makes it possible to safeguard workers in e.g. pits, water tanks, etc.

Modular

accessories:

- Intermediate
 Bracket
- Device Mounting
 bracket
- Device of your choice

Specifications:

- Weight: 10.7 kg
- Steel, galvanized
 & color coated



European standards: EN 795, class B

TankClamp max. 2 workers Art No: R010.210.020 TankClamp

Accessories Art No: R010.210.034 Intermediate bracket (Blue) Art.No: depending Device Mounting bracket



