

## EcoPolyBlend™ Spill Control Pallets

Keep workers safe from accidental slips indoors and avoid costly hazmat cleanup costs

- Protect against ground contamination.
- Comply with EPA and avoid potential fines.

Made of molded 100% recycled polyethylene, these pallets resist chemical attack from hazardous acids, caustics and solvents. The oversized sump holds the contents of up to a 55-gallon (200-liter) drum in the event of leak or rupture—meeting or exceeding the most stringent spill containment regulations. Seamless construction eliminates leaks. Self-locating grates lift off for quick cleanup. Black color hides grime and dirt to keep your workplace looking clean. Choose from square or in-line configurations. Also available in non-recycled yellow color.

EPA compliant, supports SPCC, and meets NFPA 1 2009 edition and IFC fire codes.



Use pallet as a workstation for waste collection.



**Black models - 100% recycled content.**  
Independently green validated  
by UL Environment.

Yellow models have 45% recycled content



Description	Sump Capacity Gallons/Liters	Load-bearing* Capacity lb/kg	External Dim. W x D x H	Compliance	Model No Black	Model No Yellow	Ship Wt lb/kg
2 drum in-line pallet	66/250	2500/1134	49 x 25 x 18 in	E,S,0	28623	28622	44/20
2 drum in-line pallet w/drain			1245 x 635 x 457 mm		28625	28624	
3 drum in-line pallet	75/284	3750/1701	73 x 25 x 11.625 in		28627	28626	58/26
3 drum in-line pallet w/drain			1854 x 635 x 295 mm		28629	28628	
4 drum in-line pallet	75/284	5000/2268	97 x 25 x 9 in		28631	28630	77/35
4 drum in-line pallet w/drain			2464 x 635 x 229 mm		28633	28632	
4 drum square pallet	73/276	5000/2268	49 x 49 x 10.25 in		28635	28634	70/32
4 drum square pallet w/drain			1245 x 1245 x 260 mm		28637	28636	
Ramp for 28635	—	1000/454	49 x 33 x 10.50 in 1245 x 838 x 267 mm	—	28688	28620	40/18

### EcoPolyBlend™ Replacement Grates (100% recycled)

2 drum grate for all sizes above	24 x 48 x 2.5 in 610 x 1219 x 63 mm	—	28259	—	16/7
1 drum grate for 3 drum In-line	24 x 24 x 2.5 in 610 x 610 x 63 mm		28260		8/4

\*Service temperature range: -30°F to 120°F (-34°C to 49°C)