

## **EcoPolyBlend™ Drum Management System**

## Organize drums for maximum efficiency, productivity and cost-savings

Space-saving, stackable design stores up to four 30- and/or 55-gallon (110- and/or 200-liter) drums of Class 1B or 1C flammables and combustibles or nonhazardous liquids. 100% recycled molded polyethylene construction provides maximum chemical resistance—preventing corrosion, deterioration and leaks. Molded-in drum lock-channels hold drums in place. The system consists of three parts: a base module, stack module and dispensing shelf.

**The Base Module** holds two drums with a 3060-lb (1388-kg) total load capacity. Easily relocate the base module with a forklift when empty. The 66-gallon (250-liter) open-view containment sump makes it easy to spot any spills for a quick cleanup.

**The Stack Module** holds two additional drums to double the system capacity for a load of 1500-lb (680-kg). When storing both 30- and 55-gallon (110- and 200-liter) drums, the smaller drums should be placed on the top of the stack module.

**The Dispensing Shelf** has a load capacity of 60-lb (27-kg), and mounts securely to the stack module for convenient dispensing from the upper level.

EPA compliant, supports SPCC, and meets fire codes.



EcoPolyBlend™ drum management system combines efficient drum storage and positive spill control.





28667 Base • 28669 Stacker with strap • 28671 Shelf





## Drum vents provide pressure relief . . .

Whether storing drums horizontally or vertically, Justrite has the solution for safely relieving dangerous drum pressure—visit justritemfg.com for details.









Description	Sump Capacity Gallons/Liters	Load-bearing* Capacity lb/kg	External Dim. W x D x H	Compliance	Model No Black	Model No Yellow	Ship Wt lb/kg
Base module	66/250	3060/1388	49 x 59 x 26 in 1245 x 1499 x 660 mm	E,S,0	28667	28666	138/63
Stack module	_	1500/680	49 x 46 x 12 in 1245 x 1168 x 305 mm	_	28669	28668	70/32
Dispensing shelf		60/27	19.50 x 18.75 x 16.50 in 495 x 476 x 419 mm		28671	_	12/5

<sup>\*</sup>Service temperature range: -30°F to 120°F (-34°C to 49°C)