



Type II AccuFlow™ Safety Cans

Go beyond protection and compliance with the added convenience of AccuFlow™ with Safe-Squeeze® trigger for safe and controlled pouring

- Vented design provides smooth, slug-free liquid flow
- Flexible 9-in (229-mm) long metal hose helps control the pour into small openings
- Stainless steel flame arrester prevents flashback ignition
- Two-openings – one for targeted pouring, one with ergonomically designed lift-lever for easy filling
- Sealed lid features automatic positive-pressure relief to protect against explosion
- Large label ID zone provides writing space to identify contents, department location, or individual user name
- Tough powder-coat finish resists chemicals
- Certified by FM Approvals, UL/ULC, and TÜV; meet OSHA and NFPA requirements



Description and Capacity	Hose OD x L	Can OD x H	Approv/Lstg Regulation	Red Can Model
1 gallon (4 L) steel safety can with hose	0.625 x 9 in (16 x 229 mm)	9.5 x 10.5 in (241 x 267 mm)	FM, UL/ULC, TÜV	7210120
2 gallon (7.5 L) steel safety can with hose		9.5 x 13.25 in (241 x 337 mm)		7220120
2.5 gallon (9.5 L) steel safety can with hose		11.75 x 12 in (298 x 305 mm)		7225120
5 gallon (19 L) steel safety can with hose		11.75 x 17.5 in (298 x 445 mm)		7250120
2.5 gallon (9.5 L) steel safety can with hose	1 x 9 in (25 x 229 mm)	11.75 x 12 in (298 x 305 mm)		7225130
5 gallon (19 L) steel safety can with hose		11.75 x 17.5 in (298 x 445 mm)		7250130